

Yacht	Egret	Rig	Bermudian Sloop
Sail number	GBR1390L	Design	Sweden Yachts 390
TCC	0.973	Series / built	1990 / 1995
No spinnaker fleet	0.891 <i>Mixed fleet</i> 0.966	Club(s)	CCRC HISC
Owner(s)	Patrick & Amanda Marshall		

Performance indicators

Mainsail area	36.46 m²	Sailing weight	9093 kg
Mizzen area	0.00 m²	Displacement / length	264 (Sailing weight)
Upwind headsail area	47.70 m²	Sail area / wetted surface	2.67 (main + genoa)
D/wind headsail area	99.06 m²	Sail area / displacement	19.62 (main + genoa)

Hull	source	Rig	source
Hull Length	11.88 m	Spar material	Aluminium alloy
Bow overhang	1.10 m	Forestay length	16.49 m P
Stern overhang	1.18 m	Foretriangle base	4.80 m P
Waterline length	9.60 m	Main sail	
Stern height	0.32 m	Hoist	14.90 m P
Beam	3.87 m	Foot	4.25 m P
Topside overhang	0.33 m	1/2 width	2.68 m O
Freeboard	1.16 m	3/4 width	1.49 m O
Draught	1.75 m	7/8 width	0.80 m O
Empty weight	7810 kg	Construction	Woven
Fixed ballast weight	3150 kg	Reefing	Slab
Moveable ballast	None	Upwind headsail	
		Luff length	15.50 m O
		Luff perpendicular	6.34 m O
		1/2 width	2.98 m O
		3/4 width	1.50 m O
		Foot height	0.70 m O
		Construction	Woven
		Reefing	Roller
		Downwind headsail	
		Tack type	Spinnaker pole
		Pole / tack length	4.80 m O
		* Luff length	15.05 m O
		* Leech length	15.05 m O
		* 1/2 width	7.93 m O
		* Foot width	7.93 m O
		* OR ... Area	m²

Appendages & propeller

Keel type	W3W1L1N1
Keel depth	1.11 m O
Keel chord	2.02 m O
Rudder type	Spade, partial skeg
Rudder depth	1.50 m O
Rudder chord	0.59 m O
Propeller type	Folding
Propeller blades	3
Propeller diameter	0.43 m O

Mizzen

Mizzen hoist	<i>m</i>
Mizzen foot	<i>m</i>
Staysail luff length	<i>m</i>
Staysail luff perp	<i>m</i>

Measurement source: A=Authenticated; O=Owner measured; S=Sister vessel; P=Published; C=Calculated
System data source: D=Database derived; E=Estimated **TCC calculated** on 31/03/2017 at 15:07:21

IMPORTANT: see notes on page 2 for appropriate use and validity

Certificate notes

1. Correct use of the published ratings

TCC The time correction coefficient to be used, with the following exceptions:

No spinnaker fleet To be used when competing in a class which does not permit the use of a spinnaker.

Mixed fleet To be used when rated without a spinnaker **or** when permitted to elect not to use a spinnaker **and** when competing in a class which permits the use of a spinnaker.

2. Data quality

The fairest ratings will result from accurate measurement; ratings calculated using a significant amount of estimated and published data are far more likely to be out of line with expectations than those using measured and sister ship data. Owners must notify the rating office of any changes or errors in the rating data.

3. Applicability

This certificate is issued for the sole purpose of correcting elapsed times recorded in yacht races. It is not to be used for any other purpose.

4. Validity

Unless stated to the contrary, or superseded, this certificate is valid until the end of the calendar year in which it was issued. The validity can be checked by referring to the certificates published at: www.vprs.org/ratings.html

5. Additional information

6. Stability

An SSS base value provides a guide to the stability of a boat but does not guarantee safety or freedom of risk from capsizing or sinking. The safety of a boat is the sole responsibility of the skipper who must ensure that the boat is fully found, thoroughly seaworthy, and operated by a crew sufficient in number and experience who are physically fit to face bad weather. The SSS base value does not constitute any warranty as to the seaworthiness of any boat or the safety of any gear and shall not limit the absolute responsibility of the skipper of the boat.

Guard rails fitted	Yes	
Dayboat	No	
SSS base value	40	Valid only for data on this certificate.