

Yacht	Finn	Rig	Bermudian Sloop
Sail number	103	Design	Splinter OD
TCC	0.758	Series / built	1963 / 1969
No spinnaker TCC	0.726	Default crew limit	5 people

Performance indicators

Mainsail area	8.18 m²	Sailing weight	1610 kg
Mizzen area	m²	Displacement / length	270 (sailing weight)
Upwind headsail area	9.90 m²	Sail area / wetted surface	1.66 (main + u/w headsail)
D/wind headsail area	21.41 m²	Sail area / displacement	13.38 (main + u/w headsail)

Hull

			source
Hull Length	LH	6.39 m	S
Bow overhang	BO	0.72 m	D
Stern overhang	SO	0.45 m	D
Waterline length	LWL	5.22 m	C
Stern height	Y	0.10 m	D
Beam	MB	2.08 m	P
Topside overhang	TSO	0.13 m	O
Freeboard at mast	FBI	0.60 m	D
Draught	T	1.15 m	P
Empty weight	EW	1261 kg	P
Fixed ballast weight	KW	406 kg	P
Moveable ballast		None	

Rig

Spar material		Aluminium alloy
Forestay length	FL	7.00 m D
Foretriangle base	J	2.20 m D
Mainsail hoist	P	5.83 m D
Mainsail outhaul	E	2.30 m D

Main sail

Half width	MHW	1.55 m D
Three quarter width	MTW	0.95 m D
Upper width	MUW	0.55 m D
Construction		Woven
Reefing		Slab

Upwind headsail

Luff length	HLU	6.50 m D
Luff perpendicular	HLP	3.05 m D
Half width	HHW	1.52 m D
Three quarter width	HTW	0.76 m D
Foot height	HFH	0.36 m D
Construction		Woven
Reefing		Change Sail

Downwind headsail

Tack type		Spinnaker pole
Pole / tack length	STL	2.30 m D
* Luff length	SLU	6.70 m D
* Leech length	SLE	6.70 m D
* Half width	SHW	3.85 m D
* Foot width	SFL	3.85 m D
* OR ... Area	SPA	m²

Appendages & propeller

Keel type		T3P2F2N1
Keel depth	KD	0.81 m S
Keel chord	KC	1.43 m S
Rudder type		Spade
Rudder depth	RD	0.84 m S
Rudder chord	RC	0.35 m S
Propeller type		None
Propeller blades	PRN	
Propeller diameter	PRD	m

Mizzen

Mizzen hoist	PY	m
Mizzen foot	PE	m
Staysail luff length	LLY	m
Staysail luff perp	LPY	m

Measurement source: A=Authenticated; O=Owner measured; S=Sister vessel; P=Published; C=Calculated

System data source: D=Database derived; E=Estimated

TCC calculated on 15/03/2023 at 17:09:29

IMPORTANT: see notes on page 2 for appropriate use and validity

Certificate notes

1. Correct use of the published ratings

Multiply the elapsed time by the TCC to obtain corrected time.

The TCC is calculated for the declared sail plan, which may or may not include a downwind headsail (spinnaker). For boats without a downwind headsail the words "(no spinnaker)" appear after the TCC.

Boats with a full sailplan also have a "no spinnaker TCC" for use only when racing in a non-spinnaker class.

If spinnaker and non-spinnaker boats race together, non-spinnaker boats will have an advantage on upwind legs, and a disadvantage off the wind.

2. Data quality

The fairest ratings will result from accurate measurement; ratings calculated using a significant amount of estimated and published data are far more likely to be out of line with expectations than those using measured and sister ship data. Owners must notify the rating office of any changes or errors in the rating data.

3. Applicability

This certificate is issued for the sole purpose of correcting elapsed times recorded in yacht races. It is not to be used for any other purpose.

4. Validity

Unless stated to the contrary, or superseded, this certificate is valid until the end of the calendar year in which it was issued. The validity can be checked by referring to the certificates published at: www.vprs.org/ratings.html

5. Additional information

6. Stability

An SSS base value provides a guide to the stability of a boat but does not guarantee safety or freedom of risk from capsize or sinking. The safety of a boat is the sole responsibility of the skipper who must ensure that the boat is fully found, thoroughly seaworthy, and operated by a crew sufficient in number and experience who are physically fit to face bad weather. The SSS base value does not constitute any warranty as to the seaworthiness of any boat or the safety of any gear and shall not limit the absolute responsibility of the skipper of the boat.

Guard rails fitted	Yes	
Dayboat	No	
SSS base value	12	Valid only for data on this certificate.