# STONEWAYS VPRS

Rating Certificate

Yacht	Manu (short handed)	Rig	Bermudian Sloop
Sail number	FRA38384	Design	Archambault A35
TCC	1.015	Series / built	2005 / 2011
No spinnaker TCC	0.954	Crew limit	2 people

#### **Performance indicators**

Mainsail area	<b>34.33</b> m <sup>2</sup>	Sailing weight	4951	kg
Mizzen area	$m^2$	Displacement / length	167	(sailing weight)
Upwind headsail area	<b>27.69</b> m <sup>2</sup>	Sail area / wetted surface	2.60	(main + u/w headsail)
D/wind headsail area	<b>124.52</b> m <sup>2</sup>	Sail area / displacement	21.69	(main + u/w headsail)

Hull					source
Hul	l Length	LH	10.62	m	D
Bow o	verhang	ВО	0.55	m	Α
Stern o	verhang	SO	0.82	m	Α
Waterlin	e length	LWL	9.25	m	С
Ster	n height	Υ	0.16	m	Α
	Beam	MB	3.59	m	D
Topside o	verhang	TSO	0.45	m	D
Freeboard	at mast	FBI	1.03	m	D
	Draught	T	2.16	m	D
Empty	y weight	EW	4506	kg	Α
Fixed ballas	t weight	KW	1774	kg	E
Moveable	e ballast		None		

Hull			source
Hull Length	LH	<b>10.62</b> m	D
Bow overhang	ВО	<b>0.55</b> m	Α
Stern overhang	SO	<b>0.82</b> m	Α
Waterline length	LWL	<b>9.25</b> m	С
Stern height	Y	<b>0.16</b> m	Α
Beam	MB	<b>3.59</b> m	D
Topside overhang	TSO	<b>0.45</b> m	D
Freeboard at mast	FBI	<b>1.03</b> m	D
Draught	T	<b>2.16</b> m	D
Empty weight	EW	<b>4506</b> kg	g A
Fixed ballast weight	KW	<b>1774</b> kg	g E
Moveable ballast		None	

Appendages & propelle	r		
Keel type		Z4P4L1N1	
Keel depth	KD	<b>1.71</b> m	D
Keel chord	KC	<b>0.92</b> m	D
Rudder type		Spade	
Rudder depth	RD	<b>1.53</b> m	D
Rudder chord	RC	<b>0.44</b> m	D
Propeller type		Folding	
Propeller blades	PRN	2	
Propeller diameter	PRD	<b>0.38</b> m	E

Mizzen			
Mizzen hoist	PY	m	
Mizzen foot	PE	m	
Staysail luff length	LLY	m	
Staysail luff perp	LPY	m	

Rig				
Spar material		Alum	iniu	ım alloy
Forestay length	FL	14.21	m	Α
Foretriangle base	J	4.10	m	Α
Mainsail hoist	P	13.30	m	0
Mainsail outhaul	E	4.29	m	0

Main sail			
Half width	MHW	<b>2.76</b> m	0
Three quarter width	MTW	<b>1.78</b> m	0
Upper width	MUW	<b>1.12</b> m	0
Construction		Laminated	
Reefing		Slab	

Upwind headsail			
Luff length	HLU	<b>12.28</b> m	0
Luff perpendicular	HLP	<b>4.20</b> m	0
Half width	HHW	<b>2.32</b> m	0
Three quarter width	HTW	<b>1.34</b> m	0
Foot height	HFH	<b>0.20</b> m	E
Construction		Laminated	
Reefing		Change Sail	

Downwind hea	adsail			
Т	ack type		Bow sprit	
Pole / tac	k length	STL	<b>5.50</b> m	0
* Luff length		SLU	<b>16.26</b> m	0
* Leech length		SLE	<b>14.80</b> m	0
* Half width		SHW	<b>9.50</b> m	0
* Fc	oot width	SFL	<b>10.30</b> m	0
* OR	Area	SPA	m²	

Measurement source: A=Authenticated; O=Owner measured; S=Sister vessel; P=Published; C=Calculated **System data source: D**=Database derived; **E**=Estimated TCC calculated on 09/03/2023 at 11:08:00

# Certificate notes

### 1. Correct use of the published ratings

Multiply the elapsed time by the TCC to obtain corrected time.

The TCC is calculated for the declared sail plan, which may or may not include a downwind headsail (spinnaker). For boats without a downwind headsail the words "(no spinnaker)" appear after the TCC.

Boats with a full sailplan also have a "no spinnaker TCC" for use only when racing in a non-spinnaker class.

If spinnaker and non-spinnaker boats race together, non-spinnaker boats will have an advantage on upwind legs, and a disadvantage off the wind.

#### Data quality

The fairest ratings will result from accurate measurement; ratings calculated using a significant amount of estimated and published data are far more likely to be out of line with expectations than those using measured and sister ship data. Owners must notify the rating office of any changes or errors in the rating data.

### 3. Applicability

This certificate is issued for the sole purpose of correcting elapsed times recorded in yacht races. It is not to be used for any other purpose.

### 4. Validity

Unless stated to the contrary, or superseded, this certificate is valid until the end of the calendar year in which it was issued. The validity can be checked by referring to the certificates published at: www.vprs.org/ratings.html

#### Additional information

## 6. Stability

An SSS base value provides a guide to the stability of a boat but does not guarantee safety or freedom of risk from capsize or sinking. The safety of a boat is the sole responsibility of the skipper who must ensure that the boat is fully found, thoroughly seaworthy, and operated by a crew sufficient in number and experience who are physically fit to face bad weather. The SSS base value does not constitute any warranty as to the seaworthiness of any boat or the safety of any gear and shall not limit the absolute responsibility of the skipper of the boat.

Guard rails fitted Yes

Dayboat No

**SSS base value** 26 Valid only for data on this certificate.