Α

STONEWAYS VPRS

Rating Certificate

Yacht	Neptunus Gaelle	Rig	Bermudian Sloop
Sail number	BRA126	Design	CAL 40
TCC	0.980	Series / built	1963 / 1967
No spinnaker TCC	0.935	Default crew limit	9 people

Performance indicators

Mainsail area	45.30 m ²	Sailing weight	7431	kg
Mizzen area	m^2	Displacement / length	255	(sailing weight)
Upwind headsail area	33.81 m ²	Sail area / wetted surface	2.43	(main + u/w headsail)
D/wind headsail area	121.39 m ²	Sail area / displacement	21.10	(main + u/w headsail)

Hul	I				source
	Hull Length	LH	11.87	m	D
	Bow overhang	ВО	1.45	m	Α
	Stern overhang	so	1.33	m	Α
	Waterline length	LWL	9.09	m	С
	Stern height	Y	0.42	m	Α
	Beam	MB	3.35	m	P
	Topside overhang	TSO	0.07	m	D
	Freeboard at mast	FBI	1.03	m	Α
	Draught	T	1.76	m	D
	Empty weight	EW	6280	kg	Α
	Fixed ballast weight	KW	2772	kg	P
	Moveable ballast		None		

Hull					source
	Hull Length	LH	11.87	m	D
	Bow overhang	ВО	1.45	m	Α
	Stern overhang	SO	1.33	m	Α
	Waterline length	LWL	9.09	m	С
	Stern height	Y	0.42	m	Α
	Beam	MB	3.35	m	P
	Topside overhang	TSO	0.07	m	D
	Freeboard at mast	FBI	1.03	m	Α
	Draught	T	1.76	m	D
	Empty weight	EW	6280	kg	Α
	Fixed ballast weight	KW	2772	kg	P
	Moveable ballast		None		

Appendages & propeller				
Keel type		L2P3F5N1		
Keel depth	KD	1.19 m	Α	
Keel chord	KC	3.36 m	Α	
Rudder type		Spade		
Rudder depth	RD	1.22 m	Α	
Rudder chord	RC	0.59 m	Α	
Propeller type		Folding		
Propeller blades	PRN	2		
Propeller diameter	PRD	0.48 m	Α	

Mizzen			
Mizzen hoist	PY	m	
Mizzen foot	PE	m	
Staysail luff length	LLY	m	
Staysail luff perp	LPY	m	

RIG				
	Spar material		Carbon fibre	!
	Forestay length	FL	14.40 m	0
	Foretriangle base	J	4.51 m	Α
	Mainsail hoist	P	14.20 m	Α

Mainsail outhaul

Ε

5.58 m

Main sail			
Half width	MHW	3.48 m	Α
Three quarter width	MTW	1.92 m	Α
Upper width	MUW	1.04 m	Α
Construction		Laminated	
Reefing		Slab	

Upwind headsail			
Luff length	HLU	13.92 m	Α
Luff perpendicular	HLP	4.59 m	Α
Half width	HHW	2.49 <i>m</i>	Α
Three quarter width	HTW	1.39 <i>m</i>	Α
Foot height	HFH	0.10 m	0
Construction		Laminated	
Reefing	Change Sail		

rteeling			Change	Jan
Downwind hea	adsail			
T	ack type		Spinnak	er pole
Pole / tac	k length	STL	4.55 m	Α
* Lu	ff length	SLU	16.10 m	Α
* Leec	h length	SLE	16.10 m	Α
* Half width		SHW	9.12 m	Α
* Fc	oot width	SFL	8.94 m	Α
* OR	Area	SPA	m²	2

Measurement source: A=Authenticated; O=Owner measured; S=Sister vessel; P=Published; C=Calculated **System data source: D**=Database derived; **E**=Estimated TCC calculated on 10/11/2022 at 20:30:25

IMPORTANT: see notes on page 2 for appropriate use and validity

Certificate notes

1. Correct use of the published ratings

Multiply the elapsed time by the TCC to obtain corrected time.

The TCC is calculated for the declared sail plan, which may or may not include a downwind headsail (spinnaker). For boats without a downwind headsail the words "(no spinnaker)" appear after the TCC.

Boats with a full sailplan also have a "no spinnaker TCC" for use only when racing in a non-spinnaker class.

If spinnaker and non-spinnaker boats race together, non-spinnaker boats will have an advantage on upwind legs, and a disadvantage off the wind.

2. Data quality

The fairest ratings will result from accurate measurement; ratings calculated using a significant amount of estimated and published data are far more likely to be out of line with expectations than those using measured and sister ship data. Owners must notify the rating office of any changes or errors in the rating data.

3. Applicability

This certificate is issued for the sole purpose of correcting elapsed times recorded in yacht races. It is not to be used for any other purpose.

4. Validity

Unless stated to the contrary, or superseded, this certificate is valid until the end of the calendar year in which it was issued. The validity can be checked by referring to the certificates published at: www.vprs.org/ratings.html

Additional information

6. Stability

An SSS base value provides a guide to the stability of a boat but does not guarantee safety or freedom of risk from capsize or sinking. The safety of a boat is the sole responsibility of the skipper who must ensure that the boat is fully found, thoroughly seaworthy, and operated by a crew sufficient in number and experience who are physically fit to face bad weather. The SSS base value does not constitute any warranty as to the seaworthiness of any boat or the safety of any gear and shall not limit the absolute responsibility of the skipper of the boat.

Guard rails fitted Yes

Dayboat No

SSS base value 34 Valid only for data on this certificate.