STONEWAYS VPRS

Rating Certificate

Yacht	Saga	Rig	Bermudian Sloop
Sail number	BRA333	Design	S&S One off
тсс	1.133	Series / built	1971 / 1971
No spinnaker TCC	1.102	Default crew limit	16 people

Performance indicators

Mainsail area	76.26 m ²	Sailing weight	26598	kg
Mizzen area	m^2	Displacement / length	266	(sailing weight)
Upwind headsail area	120.86 m ²	Sail area / wetted surface	3.06	(main + u/w headsail)
D/wind headsail area	234.44 m ²	Sail area / displacement	22.47	(main + u/w headsail)

Hull				source
Hull Length	LH	17.46	m	D
Bow overhang	ВО	2.30	m	D
Stern overhang	so	1.59	m	D
Waterline length	LWL	13.57	m	С
Stern height	Y	0.29	m	D
Beam	MB	4.54	m	D
Topside overhang	TSO	0.19	m	D
Freeboard at mast	FBI	1.19	m	D
Draught	Τ	3.03	m	D
Empty weight	EW	23729	kg	D
Fixed ballast weight	KW	9254	kg	E
Moveable ballast		None		

Hul					source
	Hull Length	LH	17.46	m	D
	Bow overhang	ВО	2.30	m	D
	Stern overhang	SO	1.59	m	D
	Waterline length	LWL	13.57	m	С
	Stern height	Y	0.29	m	D
	Beam	MB	4.54	m	D
	Topside overhang	TSO	0.19	m	D
	Freeboard at mast	FBI	1.19	m	D
	Draught	T	3.03	m	D
	Empty weight	EW	23729	kg	D
	Fixed ballast weight	KW	9254	kg	E
	Moveable ballast		None		

Appendages & propelle	er		
Keel type		L2P3T3N1	
Keel depth	KD	1.81 m	D
Keel chord	KC	3.07 m	D
Rudder type		Skeg hung	
Rudder depth	RD	1.90 m	D
Rudder chord	RC	1.00 m	D
Propeller type		Folding	
Propeller blades	PRN	2	
Propeller diameter	PRD	0.50 m	D

Mizzen			
Mizzen hoist	PY	m	
Mizzen foot	PE	m	
Staysail luff length	LLY	m	
Staysail luff perp	LPY	m	

Rig				
	Spar material	Aluminium alloy		n alloy
	Forestay length	FL	23.73 m	Α
	Foretriangle base	J	7.04 m	Α
	Mainsail hoist	P	20.78 m	Α
	Mainsail outhaul	E	6.13 m	Α

4
Α
Α
Α

Upwind headsail			
Luff length	HLU	22.88 m	Α
Luff perpendicular	HLP	10.58 m	Α
Half width	HHW	5.28 m	Α
Three quarter width	HTW	2.63 m	Α
Foot height	HFH	0.40 m	Α
Construction		Laminated	
Reefing	Change Sail		

rtooning			Onunge oun	
Downwind hea	adsail			
Т	ack type		Spinnaker p	ole
Pole / tac	k length	STL	7.22 m	D
* Lu	iff length	SLU	22.64 m	Α
* Leech length		SLE	22.64 m	Α
* Half width		SHW	12.58 m	Α
* Foot width		SFL	12.06 m	Α
* OR	Area	SPA	m²	

Measurement source: A=Authenticated; O=Owner measured; S=Sister vessel; P=Published; C=Calculated System data source: D=Database derived; E=Estimated TCC calculated on 08/12/2022 at 09:57:32

IMPORTANT: see notes on page 2 for appropriate use and validity

Certificate notes

1. Correct use of the published ratings

Multiply the elapsed time by the TCC to obtain corrected time.

The TCC is calculated for the declared sail plan, which may or may not include a downwind headsail (spinnaker). For boats without a downwind headsail the words "(no spinnaker)" appear after the TCC.

Boats with a full sailplan also have a "no spinnaker TCC" for use only when racing in a non-spinnaker class.

If spinnaker and non-spinnaker boats race together, non-spinnaker boats will have an advantage on upwind legs, and a disadvantage off the wind.

2. Data quality

The fairest ratings will result from accurate measurement; ratings calculated using a significant amount of estimated and published data are far more likely to be out of line with expectations than those using measured and sister ship data. Owners must notify the rating office of any changes or errors in the rating data.

3. Applicability

This certificate is issued for the sole purpose of correcting elapsed times recorded in yacht races. It is not to be used for any other purpose.

4. Validity

Unless stated to the contrary, or superseded, this certificate is valid until the end of the calendar year in which it was issued. The validity can be checked by referring to the certificates published at: www.vprs.org/ratings.html

Additional information

6. Stability

An SSS base value provides a guide to the stability of a boat but does not guarantee safety or freedom of risk from capsize or sinking. The safety of a boat is the sole responsibility of the skipper who must ensure that the boat is fully found, thoroughly seaworthy, and operated by a crew sufficient in number and experience who are physically fit to face bad weather. The SSS base value does not constitute any warranty as to the seaworthiness of any boat or the safety of any gear and shall not limit the absolute responsibility of the skipper of the boat.

Guard rails fitted Yes

Dayboat No

SSS base value 54 Valid only for data on this certificate.