### 2023

# STONEWAYS VPRS

# Rating Certificate

Yacht	Tango	Rig	Bermudian Sloop	
Sail number	GBR7469T	Design	Bolero 25.5	
тсс	0.857	Series / built	1979	
No spinnaker TCC	0.835	Default crew limit	6 people	

#### **Performance indicators**

Mainsail area	<b>16.25</b> m <sup>2</sup>	Sailing weight	1994	kg
Mizzen area	m²	Displacement / length	230	(sailing weight)
Upwind headsail area	<b>14.86</b> m <sup>2</sup>	Sail area / wetted surface	2.39	(main + u/w headsail)
D/wind headsail area	<b>30.22</b> m <sup>2</sup>	Sail area / displacement	19.96	(main + u/w headsail)

Hul	I				source
	Hull Length	LH	7.78	m	D
	Bow overhang	ВО	0.77	m	D
	Stern overhang	so	1.05	m	D
	Waterline length	LWL	5.96	m	С
	Stern height	Y	0.22	m	D
	Beam	MB	2.76	m	D
	Topside overhang	TSO	0.23	m	E
	Freeboard at mast	FBI	0.96	m	E
	Draught	T	1.48	m	D
	Empty weight	EW	1500	kg	D
	Fixed ballast weight	KW	585	kg	E
	Moveable ballast		None		

Rig			source
Spar material		Aluminium	alloy
Forestay length	FL	<b>8.08</b> m	D
Foretriangle base	J	<b>2.59</b> m	D
Mainsail hoist	P	<b>8.38</b> m	D
Mainsail outhaul	E	<b>3.27</b> m	D
Main sail			
Half width	MHW	<b>2.13</b> m	Α

Main sail			
Half width	MHW	<b>2.13</b> m	Α
Three quarter width	MTW	<b>1.24</b> m	Α
Upper width	MUW	<b>0.72</b> m	Α
Construction		Laminated	
Reefing		Slab	
Upwind headsail			

Appendages & propelle	er		
Keel type		Z1P1R1N1	
Keel depth	KD	<b>1.20</b> m	E
Keel chord	KC	<b>0.60</b> m	E
Rudder type		Skeg hung	
Rudder depth	RD	<b>1.20</b> m	E
Rudder chord	RC	<b>0.35</b> m	E
Propeller type		None	
Propeller blades	PRN		
Propeller diameter	PRD	m	

opwilla lieausali			
Luff length	HLU	<b>7.88</b> m	Α
Luff perpendicular	HLP	<b>3.77</b> <i>m</i>	Α
Half width	HHW	<b>1.89</b> m	Α
Three quarter width	HTW	<b>0.94</b> m	Α
Foot height	HFH	<b>0.05</b> m	E
Construction		Laminated	
Reefing		Change Sail	
	•		

TIND	111	
PY	m	
EY	m	
LLY	m	
LPY	m	
	EY LLY	PY m EY m LLY m

Downwind headsail					
7	Tack type	Spinnaker pole		ole	
Pole / tack length		STL	<b>2.62</b> m	D	
* Luff length		SLU	<b>7.95</b> m	Α	
* Leech length		SLE	<b>7.95</b> m	Α	
* Half width		SHW	<b>4.60</b> m	Α	
* Foot width		SFL	<b>4.50</b> m	Α	
* OR Area		SPA	$m^2$		

**Measurement source:** A=Authenticated; O=Owner measured; S=Sister vessel; P=Published; C=Calculated **System data source:** D=Database derived; E=Estimated **TCC calculated** on 26/04/2023 at 17:22:12

IMPORTANT: see notes on page 2 for appropriate use and validity

## Certificate notes

#### 1. Correct use of the published ratings

Multiply the elapsed time by the TCC to obtain corrected time.

The TCC is calculated for the declared sail plan, which may or may not include a downwind headsail (spinnaker). For boats without a downwind headsail the words "(no spinnaker)" appear after the TCC.

Boats with a full sailplan also have a "no spinnaker TCC" for use only when racing in a non-spinnaker class.

If spinnaker and non-spinnaker boats race together, non-spinnaker boats will have an advantage on upwind legs, and a disadvantage off the wind.

#### 2. Data quality

The fairest ratings will result from accurate measurement; ratings calculated using a significant amount of estimated and published data are far more likely to be out of line with expectations than those using measured and sister ship data. Owners must notify the rating office of any changes or errors in the rating data.

#### 3. Applicability

This certificate is issued for the sole purpose of correcting elapsed times recorded in yacht races. It is not to be used for any other purpose.

## 4. Validity

Unless stated to the contrary, or superseded, this certificate is valid until the end of the calendar year in which it was issued. The validity can be checked by referring to the certificates published at: www.vprs.org/ratings.html

#### Additional information

### 6. Stability

An SSS base value provides a guide to the stability of a boat but does not guarantee safety or freedom of risk from capsize or sinking. The safety of a boat is the sole responsibility of the skipper who must ensure that the boat is fully found, thoroughly seaworthy, and operated by a crew sufficient in number and experience who are physically fit to face bad weather. The SSS base value does not constitute any warranty as to the seaworthiness of any boat or the safety of any gear and shall not limit the absolute responsibility of the skipper of the boat.

Guard rails fitted Yes

Dayboat No

**SSS base value** 8 Valid only for data on this certificate.