STONEWAYS VPRS

Rating Certificate

Yacht	Tilted	Rig	Bermu	ıdian Sloop
Sail number	GBR1577N	Design	J 92s	
тсс	0.980	Series / built	1992	
No spinnaker TCC	0.931	Default crew limit	7	people

Performance indicators

Mainsail area	29.04 m ²	Sailing weight	3578	kg
Mizzen area	m^2	Displacement / length	171	(sailing weight)
Upwind headsail area	23.04 m ²	Sail area / wetted surface	2.75	(main + u/w headsail)
D/wind headsail area	85.80 m ²	Sail area / displacement	22.63	(main + u/w headsail)

I				source
Hull Length	LH	9.12	m	S
Bow overhang	ВО	0.42	m	Α
Stern overhang	so	0.67	m	Α
Waterline length	LWL	8.03	m	С
Stern height	Y	0.11	m	Α
Beam	MB	3.05	m	S
Topside overhang	TSO	0.35	m	E
Freeboard at mast	FBI	1.24	m	E
Draught	Τ	1.92	m	D
Empty weight	EW	2869	kg	Α
Fixed ballast weight	KW	1051	kg	P
Moveable ballast		None		
	Hull Length Bow overhang Stern overhang Waterline length Stern height Beam Topside overhang Freeboard at mast Draught Empty weight Fixed ballast weight	Hull Length Bow overhang Stern overhang Waterline length Stern height Y Beam Topside overhang Freeboard at mast Draught Empty weight Fixed ballast weight LWL Y BO FREEDOARD FREEDOARD	Hull Length LH 9.12 Bow overhang BO 0.42 Stern overhang SO 0.67 Waterline length LWL 8.03 Stern height Y 0.11 Beam MB 3.05 Topside overhang TSO 0.35 Freeboard at mast FBI 1.24 Draught T 1.92 Empty weight EW 2869 Fixed ballast weight KW 1051	Hull Length LH 9.12 m Bow overhang BO 0.42 m Stern overhang SO 0.67 m Waterline length LWL 8.03 m Stern height Y 0.11 m Beam MB 3.05 m Topside overhang TSO 0.35 m Freeboard at mast FBI 1.24 m Draught T 1.92 m Empty weight EW 2869 kg Fixed ballast weight KW 1051 kg

Hull			source
Hull Length	LH	9.12 m	n S
Bow overhang	ВО	0.42 m	n A
Stern overhang	so	0.67 m	n A
Waterline length	LWL	8.03 m	1 C
Stern height	Y	0.11 m	n A
Beam	MB	3.05 m	n S
Topside overhang	TSO	0.35 m	n E
Freeboard at mast	FBI	1.24 m	n E
Draught	T	1.92 m	n D
Empty weight	EW	2869 k	g A
Fixed ballast weight	KW	1051 k	g P
Moveable ballast		None	

	110110	
	H2H5F5N1	
KD	1.52 m	E
KC	0.85 m	E
	Spade	
RD	1.43 m	S
RC	0.38 m	S
	Feathering	
PRN	2	
PRD	0.35 m	E
	KD KC RD RC	#2H5F5N1 KD 1.52 m KC 0.85 m Spade RD 1.43 m RC 0.38 m Feathering PRN 2

Mizzen			
Mizzen hoist	PY	m	
Mizzen foot	PE	m	
Staysail luff length	LLY	m	
Staysail luff perp	LPY	m	

Rig				
	Spar material		Aluminium a	lloy
	Forestay length	FL	12.95 m	0
	Foretriangle base	J	3.50 m	0
	Mainsail hoist	P	11.79 m	0
	Mainsail outhaul	E	4.16 m	0

MHW	2.71 m	0
MTW	1.57 m	0
MUW	0.90 m	0
Construction Laminated		
	Slab	
	MTW	MTW 1.57 m MUW 0.90 m Laminated

Upwind headsail			
Luff length	HLU	12.16 m	0
Luff perpendicular	HLP	3.65 m	0
Half width	HHW	1.94 m	0
Three quarter width	HTW	1.02 m	0
Foot height	HFH	0.00 m	E
Construction		Laminated	
Reefing		Change Sail	

Downwind hea	adsail			
T	ack type		Bow sprit	
Pole / tac	k length	STL	5.10 m	0
* Lu	ff length	SLU	15.28 m	0
* Leech length		SLE	12.09 m	0
* H	alf width	SHW	7.56 m	0
* Fc	oot width	SFL	7.53 m	0
* OR	Area	SPA	m²	

Measurement source: A=Authenticated; O=Owner measured; S=Sister vessel; P=Published; C=Calculated **System data source: D**=Database derived; **E**=Estimated TCC calculated on 12/04/2023 at 13:57:27

IMPORTANT: see notes on page 2 for appropriate use and validity

Certificate notes

1. Correct use of the published ratings

Multiply the elapsed time by the TCC to obtain corrected time.

The TCC is calculated for the declared sail plan, which may or may not include a downwind headsail (spinnaker). For boats without a downwind headsail the words "(no spinnaker)" appear after the TCC.

Boats with a full sailplan also have a "no spinnaker TCC" for use only when racing in a non-spinnaker class.

If spinnaker and non-spinnaker boats race together, non-spinnaker boats will have an advantage on upwind legs, and a disadvantage off the wind.

2. Data quality

The fairest ratings will result from accurate measurement; ratings calculated using a significant amount of estimated and published data are far more likely to be out of line with expectations than those using measured and sister ship data. Owners must notify the rating office of any changes or errors in the rating data.

3. Applicability

This certificate is issued for the sole purpose of correcting elapsed times recorded in yacht races. It is not to be used for any other purpose.

4. Validity

Unless stated to the contrary, or superseded, this certificate is valid until the end of the calendar year in which it was issued. The validity can be checked by referring to the certificates published at: www.vprs.org/ratings.html

5. Additional information

6. Stability

An SSS base value provides a guide to the stability of a boat but does not guarantee safety or freedom of risk from capsize or sinking. The safety of a boat is the sole responsibility of the skipper who must ensure that the boat is fully found, thoroughly seaworthy, and operated by a crew sufficient in number and experience who are physically fit to face bad weather. The SSS base value does not constitute any warranty as to the seaworthiness of any boat or the safety of any gear and shall not limit the absolute responsibility of the skipper of the boat.

Guard rails fitted Yes

Dayboat No

SSS base value 19 Valid only for data on this certificate.