

Owner(s)	
email	
Telephone	Club(s)
Yacht name	Sail no.
Rig type	Series date
Design	... built
Dayboat?	ISAF compliant guardrails fitted ?

Hull source

Hull Length	LH	m
Bow overhang	BO	m
Stern overhang	SO	m
Waterline length	LWL	m
Stern height	Y	m
Beam	MB	m
Topside overhang	TSO	m
Freeboard	FBI	m
Draught	T	m
Empty weight	EW	kg
Fixed ballast weight	KW	kg
Moveable ballast		

Appendages & propeller

Keel type		
Keel depth	KD	m
Keel chord	KC	m
Rudder type		
Rudder depth	RD	m
Rudder chord	RC	m
Propeller type		
Propeller blades	PRN	
Propeller diameter	PRD	m

Mizzen

Mizzen hoist	PY	m
Mizzen foot	PE	m
Staysail luff length	LLY	m
Staysail luff perp	LPY	m

Rig source

Spar material		
Forestay length	FL	m
Foretriangle base	J	m

Main sail

Hoist	P	m
Foot	E	m
Half width	MHW	m
Three quarter width	MTW	m
Upper width	MUW	m
Construction		
Reefing		

Upwind headsail

Luff length	HLU	m
Luff perpendicular	HLP	m
Half width	HHW	m
Three quarter width	HTW	m
Foot height	HFH	m
Construction		
Reefing		

Downwind headsail

Tack type		
Pole / tack length	STL	m
* Luff length	SLU	m
* Leech length	SLE	m
* Half width	SHW	m
* Foot width	SFL	m
* OR ... Area	SPA	m ²

Refer to measurement guide ... and complete fields as appropriate; where not known, put 'X'
Data **source**: **A**=Authenticated; **O**=Owner measured; **S**=Sister ship; **P**=Published. + **Notes overleaf**

Rating application notes

IMPORTANT: these brief notes are **not** a substitute for the measurement guide.

Data source: 'S' (sister ship) is **reserved** for **authenticated data** taken from similar vessels. Where measurements are copies of those made by other owners with similar vessels, record the data source as 'O'. For waterline length only, 'C' (calculated) is also available.

Series/build dates: these are helpful when trying to source missing data.

Design: the boat type, eg: Archambault M34, Contessa 32, Humphreys 50 Custom, Sonata, X99, Elan 333, S&S 31, Melges 24 ... commonly/best used for identification.

HULL

Hull length: over the moulding only (so excludes fittings such as pulpit, bow roller etc).

Bow overhang + Stern overhang + Waterline length ... should sum to give the **Hull length**.

Beam: for a yacht with tumblehome, the maximum beam will be between points located on the topsides.

Topside overhang: taken at maximum beam; ideally port/stbd average to reduce errors arising from listing.

Freeboard: the height from the water to the deck edge adjacent to the mast.

Overhangs, stern height, freeboard: to be measured whilst afloat in the **empty weight condition** (see measurement guide). If not complied with, then please state how, so that suitable corrections may be applied.

Fixed ballast weight: that of the ballast keel, usually a published figure; declare internal ballast separately.

Moveable ballast: Canting keel / Water. Assessed on an individual basis - see below.

APPENDAGES & PROPELLER

Keel type: 8 character code as per measurement guide. Individually assessed where not fully covered.

MAINSAIL / MIZZEN

Hoist & Foot: these are rig measurements (aka P & E) - taken to bands on the mast & boom.

UPWIND HEADSAIL

Foot height: the height of the slot between deck and the upwind headsail foot mid-point, when close-hauled.

DOWNWIND HEADSAIL

* **OR ... Area:** as measured/calculated by a sailmaker for VPRS/IRC.

Common individual cases

Bilge keels

Keel depth is taken parallel to the keel surface, (ie not resolved to the vertical). Also needed is the keel contribution to the draught; the vertical distance below the lowest part of the canoe body to a horizontal plane intersecting the bottoms of the keels (ie height of canoe body above keel blocks).

Moveable ballast

Water ballast: the mass, horizontal and vertical offsets from a suitable datum point on the hull will be needed.

Canting keel: where the form/composition is adequately captured by the keel type code, then just the maximum angular displacement in degrees. Also required are the dimensions of any dagger boards.