# STONEWAYS VPRS

## Rating Certificate

Yacht	Anja Sophie	Rig	Bermudian Sloop
-------	-------------	-----	-----------------

Sail number SV174 Jeanneau 53 Design

TCC 1.005 (no spinnaker) Series / built 2008

No spinnaker TCC Default crew limit **15** people

#### **Performance indicators**

Mainsail area	<b>52.50</b> m <sup>2</sup>	Sailing weight	17928	kg
Mizzen area	$m^2$	Displacement / length	176	(sailing weight)
Upwind headsail area	<b>80.75</b> m <sup>2</sup>	Sail area / wetted surface	2.60	(main + u/w headsail)
D/wind headsail area	m²	Sail area / displacement	19.76	(main + u/w headsail)

Hu	II				source
	Hull Length	LH	15.73	m	P
	Bow overhang	ВО	0.53	m	E
	Stern overhang	so	1.24	m	E
	Waterline length	LWL	13.96	m	P
	Stern height	Y	0.35	m	E
	Beam	MB	4.77	m	P
	Topside overhang	TSO	0.40	m	E
	Freeboard at mast	FBI	1.28	m	E
	Draught	T	2.28	m	P
	Empty weight	EW	15830	kg	P
	Fixed ballast weight	KW	4985	kg	P
	Moveable ballast		None		

Hull			source
Hull Length	LH	<b>15.73</b> m	Р
Bow overhang	ВО	<b>0.53</b> m	E
Stern overhang	SO	<b>1.24</b> m	E
Waterline length	LWL	<b>13.96</b> m	P
Stern height	Y	<b>0.35</b> m	E
Beam	MB	<b>4.77</b> m	P
Topside overhang	TSO	<b>0.40</b> m	E
Freeboard at mast	FBI	<b>1.28</b> m	E
Draught	T	<b>2.28</b> m	P
Empty weight	EW	<b>15830</b> kg	P
Fixed ballast weight	KW	<b>4985</b> kg	P
Moveable ballast		None	

Appendages & propelle	er		
Keel type		H2H5R2N1	
Keel depth	KD	<b>1.53</b> m	E
Keel chord	KC	<b>1.94</b> m	E
Rudder type		Spade	
Rudder depth	RD	<b>1.53</b> m	E
Rudder chord	RC	<b>0.50</b> m	E
Propeller type		Fixed	
Propeller blades	PRN	3	
Propeller diameter	PRD	<b>0.44</b> m	E

Mizzen			
Mizzen hoist	PY	m	
Mizzen foot	EY	m	
Staysail luff length	LLY	m	
Staysail luff perp	LPY	m	

Rig				source
	Spar material		Aluminium a	alloy
	Forestay length	FL	<b>20.00</b> m	P
	Foretriangle base	J	<b>6.23</b> m	P
	Mainsail hoist	P	<b>17.50</b> m	P
	Mainsail outhaul	E	<b>6.00</b> m	P

Main sail			
Half width	MHW	<b>3.00</b> m	Ε
Three quarter width	MTW	<b>1.50</b> m	E
Upper width	MUW	<b>0.75</b> m	E
Construction		Woven	
Reefing		In-mast	
•			

Upwind headsail			
Luff length	HLU	<b>19.00</b> m	E
Luff perpendicular	HLP	<b>8.50</b> m	0
Half width	HHW	<b>4.25</b> m	E
Three quarter width	HTW	<b>2.13</b> m	E
Foot height	HFH	<b>0.40</b> m	E
Construction		Woven	
Reefing		Roller	

Downwind hea	adsail			
Т	ack type		None	
Pole / tad	k length	STL	m	
* Lu	iff length	SLU	m	
* Leech length		SLE	m	
* H	alf width	SHW	m	
* Fo	oot width	SFL	m	
* OR	Area	SPA	m²	

Measurement source: A=Authenticated; O=Owner measured; S=Sister vessel; P=Published; C=Calculated **System data source: D**=Database derived; **E**=Estimated TCC calculated on 02/05/2023 at 07:23:16

# Certificate notes

#### 1. Correct use of the published ratings

Multiply the elapsed time by the TCC to obtain corrected time.

The TCC is calculated for the declared sail plan, which may or may not include a downwind headsail (spinnaker). For boats without a downwind headsail the words "(no spinnaker)" appear after the TCC.

Boats with a full sailplan also have a "no spinnaker TCC" for use only when racing in a non-spinnaker class.

If spinnaker and non-spinnaker boats race together, non-spinnaker boats will have an advantage on upwind legs, and a disadvantage off the wind.

#### 2. Data quality

The fairest ratings will result from accurate measurement; ratings calculated using a significant amount of estimated and published data are far more likely to be out of line with expectations than those using measured and sister ship data. Owners must notify the rating office of any changes or errors in the rating data.

#### 3. Applicability

This certificate is issued for the sole purpose of correcting elapsed times recorded in yacht races. It is not to be used for any other purpose.

## 4. Validity

Unless stated to the contrary, or superseded, this certificate is valid until the end of the calendar year in which it was issued. The validity can be checked by referring to the certificates published at: www.vprs.org/ratings.html

#### Additional information

## 6. Stability

An SSS base value provides a guide to the stability of a boat but does not guarantee safety or freedom of risk from capsize or sinking. The safety of a boat is the sole responsibility of the skipper who must ensure that the boat is fully found, thoroughly seaworthy, and operated by a crew sufficient in number and experience who are physically fit to face bad weather. The SSS base value does not constitute any warranty as to the seaworthiness of any boat or the safety of any gear and shall not limit the absolute responsibility of the skipper of the boat.

Guard rails fitted Yes

Dayboat No

SSS base value 52 Valid only for data on this certificate.