STONEWAYS VPRS

Rating Certificate

Yacht	Mad Fish	Rig	Bermudian Sloop
-------	----------	-----	-----------------

Sail number GBR9381T Design **Elan 295**

TCC 0.935 Series / built 1995

TCC 2 0.902 with no downwind H/S Crew limit 7 people

Performance indicators

Mainsail area	28.95 m ²	Mizzen / mizzen staysail area	0.00	m²	/	0.00 m ²
Upwind headsail area	20.20 m ²	Displacement / length	186			
Flying headsail area	$0.00 m^2$	Sail area / wetted surface	2.51	(upwind	d sails)	
Spinnaker area	61.75 m^2	Sail area / displacement	19.31	(upwind	d sails)	

Hull & appendages			source
Hull Length	LH	9.18 m	S
Bow overhang	ВО	0.40 m	E
Stern overhang	SO	0.50 m	E
Waterline length	LWL	8.28 m	С
Stern height	Υ	0.10 m	E
Beam	MB	2.95 m	S
Topside overhang	TSO	0.28 m	E
Freeboard at mast	FBI	1.09 m	E
Draught	T	1.80 m	D
Empty weight	EW	3450 kg	D
Fixed ballast weight	KW	1000 kg	P
Moveable ballast			
Keel type		H2H5L1N	1
Keel depth	KD	1.38 m	S
Keel chord	KC	0.84 m	S
Rudder type		Spade	
Rudder depth	RD	1.49 m	S
Rudder chord	RC	0.38 m	S
Propeller type		Folding	
Propeller blades	PRN	2	
Propeller diameter	PRD	0.41 m	E

_	0.50 111	50	Otern overnang
С	8.28 m	LWL	Waterline length
E	0.10 m	Υ	Stern height
S	2.95 m	MB	Beam
E	0.28 m	TSO	Topside overhang
E	1.09 m	FBI	Freeboard at mast
D	1.80 m	T	Draught
D	3450 kg	EW	Empty weight
P	1000 kg	KW	Fixed ballast weight
			Moveable ballast
	H2H5L1N1		Keel type
S	1.38 m	KD	Keel depth
S	0.84 m	KC	Keel chord
	Spade		Rudder type
S	1.49 m	RD	Rudder depth
S	0.38 m	RC	Rudder chord
	Folding		Propeller type
	2	PRN	Propeller blades
E	0.41 m	PRD	Propeller diameter

Mizzen staysail				
Staysail luff length	LLY	m		
Stavsail luff perp	LPY	m		

	Flying headsail (downwind headsail)					
	FH lui	ff length	FHLU	m		
FH leech length			FHLE	m		
	FH ha	alf width	FHHW	m		
FH foot width		FHFL	m			
	* OR	Area	FHA	m²		

Rig				source
Spar material		Alum	iniun	n alloy
Forestay length	FL	11.67	m	S
Foretriangle base	J	3.25	m	S
Flying h/sail tack length	FHTL		m	
Spinnaker pole length	SPL	3.30	m	0
Mainsail hoist	P	11.80	m	S
Mainsail outhaul	E	4.15	m	S
Boom above sheer	BAS	1.18	m	E
Mizzen hoist	PY		m	
Mizzen outhaul	EY		m	

Main sail			
Half width	MHW	2.69 m	Α
Three quarter width	MTW	1.59 m	Α
Upper width	MUW	0.87 m	Α
Construction		Laminated	
Reefing		Slab	

Upwind headsail			
Luff length	HLU	11.12 m	Α
Luff perpendicular	HLP	3.60 m	Α
Half width	HHW	1.83 m	Α
Three quarter width	HTW	0.92 m	Α
Foot height	HFH	0.10 m	E
Construction		Laminated	
Reefing		Change Sail	

Spinnaker (downwind headsail)						
* Lu	ff length	SLU	12.00 m	0		
* Leech length		SLE	12.00 m	0		
* Half width		SHW	6.30 m	0		
* Foot width		SFL	5.80 m	0		
* OR	Area	SPA	m²			

Measurement source: A=Authenticated; O=Owner measured; S=Sister vessel; P=Published; C=Calculated **System data source: D**=Database derived; **E**=Estimated TCC calculated on 14/07/2025 at 11:35:30

IMPORTANT: see notes on page 2 for appropriate use and validity

Certificate notes

1. Correct use of the published ratings

Multiply the elapsed time by the TCC to obtain corrected time.

The TCC is calculated for the declared sail plan, which may or may not include a downwind headsail. For boats without a downwind headsail the words "(no downwind H/S)" appear after the TCC.

Boats with a full sailplan also have a "TCC 2" which excludes all downwind headsails. Strictly this is for use only when racing in a class specifically for boats without downwind headsails.

If boats with and without downwind headsails race together, the boats without downwind sails will have an advantage on upwind legs, and a disadvantage off the wind.

Data quality

The fairest ratings will result from accurate measurement; ratings calculated using a significant amount of estimated and published data are far more likely to be out of line with expectations than those using measured and sister ship data. Owners must notify the rating office of any changes or errors in the rating data.

3. Applicability

This certificate is issued for the sole purpose of correcting elapsed times recorded in yacht races. It is not to be used for any other purpose.

4. Validity

Unless stated to the contrary, or superseded, this certificate is valid until the end of the calendar year in which it was issued. The validity can be checked by referring to the certificates published at: www.vprs.org/ratings.html

Additional information

6. Stability

An SSS base value provides a guide to the stability of a boat but does not guarantee safety or freedom of risk from capsize or sinking. The safety of a boat is the sole responsibility of the skipper who must ensure that the boat is fully found, thoroughly seaworthy, and operated by a crew sufficient in number and experience who are physically fit to face bad weather. The SSS base value does not constitute any warranty as to the seaworthiness of any boat or the safety of any gear and shall not limit the absolute responsibility of the skipper of the boat.

Guard rails fitted Yes

Dayboat No

SSS base value 21 Valid only for data on this certificate.