STONEWAYS VPRS

Rating Certificate

Yacht	QT	Rig	Bermudian Sloop
Sail number	GBR1972	Design	Ecume de Mer
тсс	0.834	Series / built	1970 / 1972
No spinnaker TCC	0.797	Default crew limit	6 people

Performance indicators

Mainsail area	15.14 m ²	Sailing weight	2629	kg
Mizzen area	m²	Displacement / length	335	(sailing weight)
Upwind headsail area	15.10 m ²	Sail area / wetted surface	2.34	(main + u/w headsail)
D/wind headsail area	44.47 m ²	Sail area / displacement	16.13	(main + u/w headsail)

Hull			source
Hull Length	LH	7.90 m	0
Bow overhang	ВО	1.19 m	Α
Stern overhang	so	0.97 m	Α
Waterline length	LWL	5.74 m	С
Stern height	Υ	0.26 m	Α
Beam	MB	2.66 m	0
Topside overhang	TSO	0.22 m	E
Freeboard at mast	FBI	0.97 m	E
Draught	T	1.52 m	P
Empty weight	EW	2080 kg	Α
Fixed ballast weight	KW	730 kg	P
Moveable ballast			

				source
Hull Length	LH	7.90	m	0
Bow overhang	ВО	1.19	m	Α
Stern overhang	SO	0.97	m	Α
Waterline length	LWL	5.74	m	С
Stern height	Υ	0.26	m	Α
Beam	MB	2.66	m	0
Topside overhang	TSO	0.22	m	E
Freeboard at mast	FBI	0.97	m	E
Draught	T	1.52	m	P
Empty weight	EW	2080	kg	Α
Fixed ballast weight	KW	730	kg	P
Moveable ballast				
	Hull Length Bow overhang Stern overhang Waterline length Stern height Beam Topside overhang Freeboard at mast Draught Empty weight	Hull Length Bow overhang SO Stern overhang Waterline length Stern height Y Beam MB Topside overhang TSO Freeboard at mast Draught T Empty weight EW Fixed ballast weight	Hull Length LH 7.90 Bow overhang BO 1.19 Stern overhang SO 0.97 Waterline length LWL 5.74 Stern height Y 0.26 Beam MB 2.66 Topside overhang TSO 0.22 Freeboard at mast FBI 0.97 Draught T 1.52 Empty weight EW 2080 Fixed ballast weight KW 730	Hull Length LH 7.90 m Bow overhang BO 1.19 m Stern overhang SO 0.97 m Waterline length LWL 5.74 m Stern height Y 0.26 m Beam MB 2.66 m Topside overhang TSO 0.22 m Freeboard at mast FBI 0.97 m Draught T 1.52 m Empty weight EW 2080 kg Fixed ballast weight KW 730 kg

Appendages & propeller				
Keel type	;	Z1P1R	21N1	
Keel depth	KD	1.10	m E	
Keel chord	I KC	0.63	m E	
Rudder type	;	Skeg l	nung	
Rudder depth	n RD	1.10	m E	
Rudder chord	I RC	0.40	m E	
Propeller type	:	Foldin	g	
Propeller blades	PRN	2		
Propeller diameter	PRD	0.31	m E	

Mizzen			
Mizzen hoist	PY	m	
Mizzen foot	PE	m	
Staysail luff length	LLY	m	
Staysail luff perp	LPY	m	

Rig				
	Spar material	Aluminium alloy		
	Forestay length	FL	10.31 n	n A
	Foretriangle base	J	2.80 n	n A
	Mainsail hoist	P	9.20 n	n A
	Mainsail outhaul	E	2.80 n	n A

Main sail			
Half width	MHW	1.80 m	Α
Three quarter width	MTW	1.05 m	Α
Upper width	MUW	0.59 m	Α
Construction		Laminated	
Reefing		Slab	

Upwing neadsail			
Luff length	HLU	9.65 m	Α
Luff perpendicular	HLP	3.01 m	Α
Half width	HHW	1.60 m	Α
Three quarter width	HTW	0.85 m	Α
Foot height	HFH	0.12 m	0
Construction		Laminated	
Reefing		Change Sail	
			•

Downwind hea	adsail			
Т	ack type		Spinnaker p	ole
Pole / tack length		STL	2.98 m	Α
* Lu	iff length	SLU	9.63 m	Α
* Leech length		SLE	9.63 m	Α
* Half width		SHW	5.60 m	Α
* Foot width		SFL	5.42 m	Α
* OR	Area	SPA	m²	

Measurement source: A=Authenticated; O=Owner measured; S=Sister vessel; P=Published; C=Calculated System data source: D=Database derived; E=Estimated TCC calculated on 14/01/2023 at 15:23:39

IMPORTANT: see notes on page 2 for appropriate use and validity

Certificate notes

1. Correct use of the published ratings

Multiply the elapsed time by the TCC to obtain corrected time.

The TCC is calculated for the declared sail plan, which may or may not include a downwind headsail (spinnaker). For boats without a downwind headsail the words "(no spinnaker)" appear after the TCC.

Boats with a full sailplan also have a "no spinnaker TCC" for use only when racing in a non-spinnaker class.

If spinnaker and non-spinnaker boats race together, non-spinnaker boats will have an advantage on upwind legs, and a disadvantage off the wind.

2. Data quality

The fairest ratings will result from accurate measurement; ratings calculated using a significant amount of estimated and published data are far more likely to be out of line with expectations than those using measured and sister ship data. Owners must notify the rating office of any changes or errors in the rating data.

3. Applicability

This certificate is issued for the sole purpose of correcting elapsed times recorded in yacht races. It is not to be used for any other purpose.

4. Validity

Unless stated to the contrary, or superseded, this certificate is valid until the end of the calendar year in which it was issued. The validity can be checked by referring to the certificates published at: www.vprs.org/ratings.html

5. Additional information

6. Stability

An SSS base value provides a guide to the stability of a boat but does not guarantee safety or freedom of risk from capsize or sinking. The safety of a boat is the sole responsibility of the skipper who must ensure that the boat is fully found, thoroughly seaworthy, and operated by a crew sufficient in number and experience who are physically fit to face bad weather. The SSS base value does not constitute any warranty as to the seaworthiness of any boat or the safety of any gear and shall not limit the absolute responsibility of the skipper of the boat.

Guard rails fitted Yes

Dayboat No

SSS base value 19 Valid only for data on this certificate.