# 2023

# STONEWAYS VPRS

## Rating Certificate

Yacht	Scaramouche	Rig	Beri	mudian Sloop
Sail number	F738	Design	Nor	dic Folkboat OD
TCC	0.780	Series / built		
No spinnaker TCC	0.760	Default crew limit	5	people

#### **Performance indicators**

Mainsail area	16.72 m <sup>2</sup>	Sailing weight	2370	kg
Mizzen area	m²	Displacement / length	249	(sailing weight)
Upwind headsail area	<b>7.38</b> m <sup>2</sup>	Sail area / wetted surface	1.41	(main + u/w headsail)
D/wind headsail area	<b>19.30</b> m <sup>2</sup>	Sail area / displacement	13.78	(main + u/w headsail)

Hull			source
Hull Length	LH	<b>7.68</b> m	Р
Bow overhang	ВО	<b>0.92</b> m	E
Stern overhang	so	<b>0.76</b> m	E
Waterline length	LWL	<b>6.00</b> m	P
Stern height	Y	<b>0.12</b> m	E
Beam	MB	<b>2.20</b> m	P
Topside overhang	TSO	<b>0.18</b> m	E
Freeboard at mast	FBI	<b>0.60</b> m	E
Draught	Τ	<b>1.20</b> m	P
Empty weight	EW	<b>1930</b> kg	P
Fixed ballast weight	KW	<b>1031</b> kg	P
Moveable ballast		None	

Rig				source
	Spar material		Timber	
	Forestay length	FL	<b>6.80</b> m	P
	Foretriangle base	J	<b>2.00</b> m	P
	Mainsail hoist	P	<b>8.75</b> m	P
	Mainsail outhaul	E	<b>3.40</b> m	P

Main sail			
Half width	MHW	<b>2.06</b> m	P
Three quarter width	MTW	<b>1.14</b> m	P
Upper width	MUW	<b>0.60</b> m	E
Construction		Woven	
Reefing		Slab	
Upwind headsail			

Appendages & propelle	er		
Keel type		L1P3F4N1	
Keel depth	KD	<b>0.75</b> m	S
Keel chord	KC	<b>3.76</b> m	S
Rudder type		Keel Hung	
Rudder depth	RD	<b>1.12</b> m	S
Rudder chord	RC	<b>0.67</b> m	S
Propeller type		None	
Propeller blades	PRN		
Propeller diameter	PRD	m	

Opmina noadodii			
Luff length	HLU	<b>6.25</b> m	Р
Luff perpendicular	HLP	<b>2.36</b> m	P
Half width	HHW	<b>1.18</b> m	Ε
Three quarter width	HTW	<b>0.59</b> m	Ε
Foot height	HFH	<b>0.00</b> m	Ε
Construction		Woven	
Reefing	g <b>Change Sail</b>		

Mizzen			
Mizzen hoist	PY	m	
Mizzen foot	EY	m	
Staysail luff length	LLY	m	
Staysail luff perp	LPY	m	

Downwind headsail						
Т	Tack type		Spinnaker pole			
Pole / tack length		STL	<b>2.05</b> m	P		
* Luff length		SLU	<b>6.46</b> m	P		
* Leech length		SLE	<b>6.46</b> m	P		
* Half width		SHW	<b>3.60</b> m	P		
* Foot width		SFL	<b>3.60</b> m	P		
* OR	Area	SPA	m²			

Measurement source: A=Authenticated; O=Owner measured; S=Sister vessel; P=Published; C=Calculated

System data source: D=Database derived; E=Estimated

TCC calculated on 17/05/2023 at 08:24:42

IMPORTANT: see notes on page 2 for appropriate use and validity

## Certificate notes

#### 1. Correct use of the published ratings

Multiply the elapsed time by the TCC to obtain corrected time.

The TCC is calculated for the declared sail plan, which may or may not include a downwind headsail (spinnaker). For boats without a downwind headsail the words "(no spinnaker)" appear after the TCC.

Boats with a full sailplan also have a "no spinnaker TCC" for use only when racing in a non-spinnaker class.

If spinnaker and non-spinnaker boats race together, non-spinnaker boats will have an advantage on upwind legs, and a disadvantage off the wind.

#### Data quality

The fairest ratings will result from accurate measurement; ratings calculated using a significant amount of estimated and published data are far more likely to be out of line with expectations than those using measured and sister ship data. Owners must notify the rating office of any changes or errors in the rating data.

#### 3. Applicability

This certificate is issued for the sole purpose of correcting elapsed times recorded in yacht races. It is not to be used for any other purpose.

## 4. Validity

Unless stated to the contrary, or superseded, this certificate is valid until the end of the calendar year in which it was issued. The validity can be checked by referring to the certificates published at: www.vprs.org/ratings.html

#### Additional information

## 6. Stability

An SSS base value provides a guide to the stability of a boat but does not guarantee safety or freedom of risk from capsize or sinking. The safety of a boat is the sole responsibility of the skipper who must ensure that the boat is fully found, thoroughly seaworthy, and operated by a crew sufficient in number and experience who are physically fit to face bad weather. The SSS base value does not constitute any warranty as to the seaworthiness of any boat or the safety of any gear and shall not limit the absolute responsibility of the skipper of the boat.

Guard rails fitted Yes

Dayboat No

SSS base value 18 Valid only for data on this certificate.