VPRS

2021 Rating Certificate

www.vprs.org

Yacht	Scarlet Jester			Rig	Bermudian Sloop		
Sail number	GBR5678T			Design	SJ 320		
TCC	0.964			Series / built	1994 / 1995		
No spinnaker TCC	0.929			Club(s) / Events(s)	PYC		
Performance indicator	S						
Mainsail area	31.89 m ²			Sailing weight	4043 kg		
Mizzen area	m²			Displacement / length	197 (sailing weight)		
Upwind headsail area	22.08 m ²			Sail area / wetted surface	2.69 (main + u/w headsail)		
D/wind headsail area	71.75 m ²			Sail area / displacement	21.61 (main + u/w headsail)		
Hull			source	Rig			source
Hull Length	LH	9.51 m	D	Spar material		Aluminium a	alloy
Bow overhang	ВО	0.83 m	Α	Forestay length	FL	12.46 m	Α
Stern overhang	so	0.72 m	Α	Foretriangle base	J	3.46 m	Α
Waterline length	LWL	7.96 m	С	Main sail			
Stern height	Y	0.13 m	Α	Hoist	P	12.17 m	Α
Beam	MB	3.15 m	D	Foot	E	4.57 m	Α
Topside overhang	TSO	0.35 m	D	Half width	MHW	2.80 m	Α
Freeboard at mast	FBI	1.10 m	D	Three quarter width	MTW	1.67 m	Α
Draught	T	1.95 m	D	Upper width	MUW	0.92 m	Α
Empty weight	EW	3272 kg	Α	Construction		Laminated	
Fixed ballast weight	KW	1276 kg	E	Reefing		Slab	
Moveable ballast		None		Upwind headsail			
Appendages & propell	er			Luff length	HLU	11.73 m	Α
Keel type		H2H5R2N	1	Luff perpendicular	HLP	3.58 <i>m</i>	Α
Keel depth	KD	1.53 m	D	Half width	HHW	1.92 m	Α
Keel chord	KC	0.89 m	D	Three quarter width	HTW	1.07 m	Α
Rudder type		Spade		Foot height	HFH	0.10 m	Ε
Rudder depth	RD	1.53 m	D	Construction		Laminated	
Rudder chord	RC	0.45 m	D	Reefing		Change Sail	
Propeller type		Folding		Downwind headsail			
Propeller blades	PRN	2		Tack type		Spinnaker p	ole
Propeller diameter	PRD	0.41 m	E	Pole / tack length	STL	3.68 m	Α
Mizzen				* Luff length	SLU	12.56 m	Α
Mizzen hoist	PY	m		* Leech length	SLE	12.57 m	Α
Mizzen foot	PE	m		* Half width	SHW	7.00 m	Α
Staysail luff length	LLY	m		* Foot width	SFL	6.40 m	Α
Staysail luff perp	LPY	m		* OR Area	SPA	m²	

Measurement source: A=Authenticated; O=Owner measured; S=Sister vessel; P=Published; C=Calculated **System data source:** D=Database derived; E=Estimated **TCC calculated** on 08/06/2021 at 16:02:59

IMPORTANT: see notes on page 2 for appropriate use and validity

Certificate notes

1. Correct use of the published ratings

Multiply the elapsed time by the TCC to obtain corrected time.

The TCC is calculated for the declared sail plan, which may or may not include a downwind headsail (spinnaker). For boats without a downwind headsail the words "(no spinnaker)" appear after the TCC.

Boats with a full sailplan also have a "no spinnaker TCC" for use only when racing in a non-spinnaker class.

If spinnaker and non-spinnaker boats race together, non-spinnaker boats will have an advantage on upwind legs, and a disadvantage off the wind.

2. Data quality

The fairest ratings will result from accurate measurement; ratings calculated using a significant amount of estimated and published data are far more likely to be out of line with expectations than those using measured and sister ship data. Owners must notify the rating office of any changes or errors in the rating data.

3. Applicability

This certificate is issued for the sole purpose of correcting elapsed times recorded in yacht races. It is not to be used for any other purpose.

4. Validity

Unless stated to the contrary, or superseded, this certificate is valid until the end of the calendar year in which it was issued. The validity can be checked by referring to the certificates published at: www.vprs.org/ratings.html

Additional information

6. Stability

An SSS base value provides a guide to the stability of a boat but does not guarantee safety or freedom of risk from capsize or sinking. The safety of a boat is the sole responsibility of the skipper who must ensure that the boat is fully found, thoroughly seaworthy, and operated by a crew sufficient in number and experience who are physically fit to face bad weather. The SSS base value does not constitute any warranty as to the seaworthiness of any boat or the safety of any gear and shall not limit the absolute responsibility of the skipper of the boat.

Guard rails fitted Yes

Dayboat No

SSS base value 21 Valid only for data on this certificate.