STONEWAYS VPRS

Rating Certificate

Yacht	Temptation	Rig	Bermudian Sloop
Sail number	GBR3321T	Design	Evolution 26
тсс	0.853	Series / built	1978 / 1979
No spinnaker TCC	0.817	Default crew limit	6 people

Performance indicators

Mainsail area	17.19 m ²	Sailing weight	2718	kg
Mizzen area	m^2	Displacement / length	214	(sailing weight)
Upwind headsail area	14.43 m ²	Sail area / wetted surface	2.07	(main + u/w headsail)
D/wind headsail area	41.48 m ²	Sail area / displacement	16.50	(main + u/w headsail)

Hull				source
Hull Length	LH	7.86	m	0
Bow overhang	ВО	0.80	m	0
Stern overhang	so	0.18	m	0
Waterline length	LWL	6.88	m	0
Stern height	Y	0.05	m	E
Beam	MB	2.84	m	0
Topside overhang	TSO	0.24	m	E
Freeboard at mast	FBI	0.96	m	E
Draught	T	1.52	m	P
Empty weight	EW	2186	kg	P
Fixed ballast weight	KW	730	kg	P
Moveable ballast		None		

Hull Length	LH	7.86	m	0
Bow overhang	ВО	0.80	m	0
Stern overhang	SO	0.18	m	0
Waterline length	LWL	6.88	m	0
Stern height	Y	0.05	m	E
Beam	MB	2.84	m	0
Topside overhang	TSO	0.24	m	E
Freeboard at mast	FBI	0.96	m	E
Draught	T	1.52	m	P
Empty weight	EW	2186	kg	P
Fixed ballast weight	KW	730	kg	P
Moveable ballast		None		

Appendages & propelle	r		
Keel type		Z4P1R1L1	
Keel depth	KD	1.19 m	0
Keel chord	KC	0.66 m	0
Rudder type		Lifting trans	om hung
Rudder depth	RD	1.20 m	Ε
Rudder chord	RC	0.41 m	Ε
Propeller type		Folding	
Propeller blades	PRN	2	
Propeller diameter	PRD	0.33 m	0

Mizzen			
Mizzen hoist	PY	m	
Mizzen foot	PE	m	
Staysail luff length	LLY	m	
Staysail luff perp	LPY	m	

Rig				
	Spar material	Spar material Aluminium alloy		alloy
	Forestay length	FL	9.30 m	0
	Foretriangle base	J	2.96 m	0
	Mainsail hoist	P	9.25 m	0
	Mainsail outhaul	E	3.15 m	0

Main sail			
Half width	MHW	2.04 m	0
Three quarter width	MTW	1.19 m	0
Upper width	MUW	0.66 m	0
Construction		Laminated	
Reefing		Slab	

Upwind headsail			
Luff length	HLU	9.05 m	0
Luff perpendicular	HLP	3.11 m	0
Half width	HHW	1.62 m	0
Three quarter width	HTW	0.84 m	0
Foot height	HFH	0.05 m	
Construction		Laminated	
Reefing		Change Sail	

Downwind hea	adsail			
T	ack type		Spinnaker po	ole
Pole / tac	k length	STL	2.96 m	0
* Luff length		SLU	m	
* Leech length		SLE	m	
* Half width		SHW	m	
* Foot width		SFL	m	
* OR	Area	SPA	41.48 m ²	0

Measurement source: A=Authenticated; O=Owner measured; S=Sister vessel; P=Published; C=Calculated **System data source: D**=Database derived; **E**=Estimated TCC calculated on 08/04/2022 at 10:48:51

IMPORTANT: see notes on page 2 for appropriate use and validity

Certificate notes

1. Correct use of the published ratings

Multiply the elapsed time by the TCC to obtain corrected time.

The TCC is calculated for the declared sail plan, which may or may not include a downwind headsail (spinnaker). For boats without a downwind headsail the words "(no spinnaker)" appear after the TCC.

Boats with a full sailplan also have a "no spinnaker TCC" for use only when racing in a non-spinnaker class.

If spinnaker and non-spinnaker boats race together, non-spinnaker boats will have an advantage on upwind legs, and a disadvantage off the wind.

Data quality

The fairest ratings will result from accurate measurement; ratings calculated using a significant amount of estimated and published data are far more likely to be out of line with expectations than those using measured and sister ship data. Owners must notify the rating office of any changes or errors in the rating data.

3. Applicability

This certificate is issued for the sole purpose of correcting elapsed times recorded in yacht races. It is not to be used for any other purpose.

4. Validity

Unless stated to the contrary, or superseded, this certificate is valid until the end of the calendar year in which it was issued. The validity can be checked by referring to the certificates published at: www.vprs.org/ratings.html

Additional information

6. Stability

An SSS base value provides a guide to the stability of a boat but does not guarantee safety or freedom of risk from capsize or sinking. The safety of a boat is the sole responsibility of the skipper who must ensure that the boat is fully found, thoroughly seaworthy, and operated by a crew sufficient in number and experience who are physically fit to face bad weather. The SSS base value does not constitute any warranty as to the seaworthiness of any boat or the safety of any gear and shall not limit the absolute responsibility of the skipper of the boat.

Guard rails fitted Yes

Dayboat No

SSS base value 15 Valid only for data on this certificate.