STONEWAYS VPRS

Rating Certificate

Yacht	Ventaneiro 3	Rig	Bermudian Sloop
Sail number	BRA2505	Design	Dufour 500
тсс	1.091	Series / built	2010 / 2013
No spinnaker TCC	1.024	Default crew limit	14 people

Performance indicators

Mainsail area	57.98 m ²	Sailing weight	17365	kg
Mizzen area	m²	Displacement / length	175	(sailing weight)
Upwind headsail area	58.79 m ²	Sail area / wetted surface	2.27	(main + u/w headsail)
D/wind headsail area	207.63 m ²	Sail area / displacement	17.69	(main + u/w headsail)

Hul	I				source
	Hull Length	LH	14.75	m	D
	Bow overhang	ВО	0.17	m	D
	Stern overhang	so	0.82	m	D
	Waterline length	LWL	13.76	m	С
	Stern height	Y	0.17	m	D
	Beam	MB	4.80	m	D
	Topside overhang	TSO	0.39	m	D
	Freeboard at mast	FBI	1.50	m	D
	Draught	T	2.30	m	D
	Empty weight	EW	15071	kg	Α
	Fixed ballast weight	KW	5800	kg	E
	Moveable ballast		None		

ıll			source
Hull Length	LH	14.75 m	D
Bow overhang	ВО	0.17 m	D
Stern overhang	so	0.82 m	D
Waterline length	LWL	13.76 m	С
Stern height	Y	0.17 m	D
Beam	MB	4.80 m	D
Topside overhang	TSO	0.39 m	D
Freeboard at mast	FBI	1.50 m	D
Draught	T	2.30 m	D
Empty weight	EW	15071 kg	Α
Fixed ballast weight	KW	5800 kg	E
Moveable ballast		None	

Appendages & propelle	er		
Keel type		H2H5R2N1	
Keel depth	KD	1.67 m	D
Keel chord	KC	1.68 m	D
Rudder type		Spade	
Rudder depth	RD	1.92 m	D
Rudder chord	RC	0.59 m	D
Propeller type		Folding	
Propeller blades	PRN	3	
Propeller diameter	PRD	0.53 m	Α

Mizzen			
Mizzen hoist	PY	m	
Mizzen foot	PE	m	
Staysail luff length	LLY	m	
Staysail luff perp	LPY	m	

Rig				
	Spar material		Aluminium a	lloy
	Forestay length	FL	19.27 m	Α
	Foretriangle base	J	5.34 m	Α
	Mainsail hoist	P	17.46 m	Α
	Mainsail outhaul	E	5.50 m	Α

Main sail			
Half width	MHW	3.66 m	Α
Three quarter width	MTW	2.21 m	Α
Upper width	MUW	1.27 m	Α
Construction		Laminated	
Reefing		Slab	

Upwind headsail			
Luff length	HLU	17.87 m	Α
Luff perpendicular	HLP	5.98 m	Α
Half width	HHW	3.46 m	Α
Three quarter width	HTW	1.99 m	Α
Foot height	HFH	0.20 m	E
Construction		Laminated	
Reefing		Change Sail	

Downwind hea	adsail			
Т	ack type		Bow sprit	
Pole / tack length		STL	6.43 m	Α
* Luff length		SLU	21.41 m	Α
* Leech length		SLE	19.03 m	Α
* Half width		SHW	12.24 m	Α
* Foot width		SFL	12.90 m	Α
* OR	Area	SPA	m²	

Measurement source: A=Authenticated; O=Owner measured; S=Sister vessel; P=Published; C=Calculated **System data source: D**=Database derived; **E**=Estimated TCC calculated on 07/11/2022 at 10:35:56

IMPORTANT: see notes on page 2 for appropriate use and validity

Certificate notes

1. Correct use of the published ratings

Multiply the elapsed time by the TCC to obtain corrected time.

The TCC is calculated for the declared sail plan, which may or may not include a downwind headsail (spinnaker). For boats without a downwind headsail the words "(no spinnaker)" appear after the TCC.

Boats with a full sailplan also have a "no spinnaker TCC" for use only when racing in a non-spinnaker class.

If spinnaker and non-spinnaker boats race together, non-spinnaker boats will have an advantage on upwind legs, and a disadvantage off the wind.

2. Data quality

The fairest ratings will result from accurate measurement; ratings calculated using a significant amount of estimated and published data are far more likely to be out of line with expectations than those using measured and sister ship data. Owners must notify the rating office of any changes or errors in the rating data.

3. Applicability

This certificate is issued for the sole purpose of correcting elapsed times recorded in yacht races. It is not to be used for any other purpose.

4. Validity

Unless stated to the contrary, or superseded, this certificate is valid until the end of the calendar year in which it was issued. The validity can be checked by referring to the certificates published at: www.vprs.org/ratings.html

Additional information

6. Stability

An SSS base value provides a guide to the stability of a boat but does not guarantee safety or freedom of risk from capsize or sinking. The safety of a boat is the sole responsibility of the skipper who must ensure that the boat is fully found, thoroughly seaworthy, and operated by a crew sufficient in number and experience who are physically fit to face bad weather. The SSS base value does not constitute any warranty as to the seaworthiness of any boat or the safety of any gear and shall not limit the absolute responsibility of the skipper of the boat.

Guard rails fitted Yes

Dayboat No

SSS base value 58 Valid only for data on this certificate.